

Annex to certificate HAF 1511126 C001

Project:

Mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves

Customer: HAFNER Pneumatika Kft. Halászi Hungary

Contract Number: Q15/11-126-C Report No.: Q15/11-126-C R004 Version V3, Revision R1, January 2024

Peter Söderblom



Table of Contents

1	Purpose and Scope	3
2	Variants	3
	2.1 Failure rates	
3	Status of the Document	14
	3.1 Liability	14
	3.2 Releases	
	3.3 Future Enhancements	14
	3.4 Release Signatures	14



1 Purpose and Scope

This document lists the versions of the assessed valves together with their respective failure rates. Normally these are registered on the certificate itself but as this assessment was performed for so many variants, the numbers are maintained in this annex instead.

2 Variants

The mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves can be considered to be part of a Type A element with a hardware fault tolerance of 0.

Tables 1 – 16 gives an overview of the different variants that belong to the considered mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves.

For safety applications only the described variants in Tables 1 - 16 of of the mechanically actuated valves, direct operated solenoid valves, pneumatically operated valves and pilot operated solenoid valves working as DTT (De-energize To Trip) devices have been considered.

Table 1: [V1] Mechanically actuated 3/2-way valves

Name	Description
BR 311	Mechanically actuated 3/2-way roller lever valves
BR 311 VES	Mechanically actuated 3/2-way roller lever valves, stainless steel
BV 311	Mechanically actuated 3/2-way stem valves
BV 311 VES	Mechanically actuated 3/2-way stem valves, stainless steel
BV 311 TT	Mechanically actuated 3/2-way stem valves for low temperature
BV 311 11	(with unidirectional sealing)
BL 311	Mechanically actuated 3/2-way roller lever valves with idle return
BG 311	Mechanically actuated 3/2-way stem actuated spool valves
BG 311 TT	Mechanically actuated 3/2-way stem actuated spool valves for
BG 311 11	low temperature (with unidirectional sealing)
BG 311 TT AIR	Mechanically actuated 3/2-way stem actuated spool valves for
	low temperature (with bidirectional sealing)

Table 2 [V2] Mechanically actuated 5/2-way valves

Name	Description
BR 511	Mechanically actuated 5/2-way roller lever valves
BR 511 VES	Mechanically actuated 5/2-way roller lever valves, stainless steel
BV 511	Mechanically actuated 5/2-way stem valves
BV 511 VES	Mechanically actuated 5/2-way stem valves, stainless steel
BV 311 TT	Mechanically actuated 3/2-way stem valves for low temperature (with unidirectional sealing)
BL 511	Mechanically actuated 5/2-way roller lever valves with idle return



Table 3 [V3] Direct operated 2/2-way and 3/2-way solenoid valves

Name	Description
M 211	Direct actuated in-line 2/2-way solenoid valves
M 211 VES	Direct actuated in-line 2/2-way solenoid valves, stainless steel
M 311	Direct actuated in-line 3/2-way solenoid valves
M311 VES	Direct actuated in-line 3/2-way solenoid valves, stainless steel
M 311 TT	Direct actuated in-line 3/2-way solenoid valves for low temperature (with unidirectional sealing)

Table 4 [V4] Pneumatically operated 2/2-way and 3/2-way valves

Name	Description
P 210	Pneumatically actuated 2/2-way spool valves
P 211	Pneumatically actuated 2/2-way spool valves with mechanical
	spring return
P 210 VES	Pneumatically actuated 2/2-way spool valves, stainless steel
P 211 VES	Pneumatically actuated 2/2-way spool valves with mechanical
1 211 VEO	spring return stainless steel
P 210 TT	Pneumatically actuated 2/2-way spool valves for low
1 210 11	temperature (with unidirectional sealing)
P 211 TT	Pneumatically actuated 2/2-way spool valves with mechanical
211 11	spring return (with unidirectional sealing)
P 210 VIT	Pneumatically actuated 2/2-way spool valves with FPM/FKM
	sealings
P 211 VIT	Pneumatically actuated 2/2-way spool valves with mechanical
	spring return, with FPM/FKM sealings
P 210 NT	Pneumatically actuated 2/2-way spool valves for -20°C
P 211 NT	Pneumatically actuated 2/2-way spool valves with mechanical
	spring return for -20°C
P 211 SR	Pneumatically actuated 2/2-way spool valves with mechanical
	spring return, with adjustable pneumatic pressure switch
P 211 SR VIT	Pneumatically actuated 2/2-way spool valves with mechanical
P 211 3R VII	spring return, with adjustable pneumatic pressure switch with FPM/FKM sealings
	Pneumatically actuated 2/2-way spool valves with mechanical
P 211 SR NT	spring return, with adjustable pneumatic pressure switch for -
	20°C
	Pneumatically actuated 2/2-way spool valves with mechanical
P 211 SR 02 NTB	spring return, with adjustable pneumatic pressure switch for -
	25°C
P 310	Pneumatically actuated 3/2-way spool valves
P 311	Pneumatically actuated 3/2-way spool valves with mechanical
	spring return
P 310 VES	Pneumatically actuated 3/2-way spool valves, stainless steel
P 311 VES	Pneumatically actuated 3/2-way spool valves with mechanical
1 011 120	spring return stainless steel
P 310 TT	Pneumatically actuated 3/2-way spool valves for low
	temperature (with unidirectional sealing)
P 311 TT	Pneumatically actuated 3/2-way spool valves with mechanical
	spring return (with unidirectional sealing)
P 310 TT AIR	Pneumatically actuated 3/2-way spool valves for low
	temperature (with bidirectional sealing)



Name	Description
P 311 TT AIR	Pneumatically actuated 3/2-way spool valves with mechanical spring return (with bidirectional sealing)
P 310 VIT	Pneumatically actuated 3/2-way spool valves with FPM/FKM sealings
P 311 VIT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with FPM/FKM sealings
P 310 NT	Pneumatically actuated 3/2-way spool valves for -20°C
P 311 NT	Pneumatically actuated 3/2-way spool valves with mechanical spring return for -20°C
P 311 SR	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch
P 311 SR VIT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch with FPM/FKM sealings
P 311 SR NT	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for - 20°C
P 311 SR 02 NTB	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch for - 25°C
P 311 SR VES	Pneumatically actuated 3/2-way spool valves with mechanical spring return, with adjustable pneumatic pressure switch, stainless steel
P 311 NTB	Pneumatically actuated 3/2-way spool valves with mechanical spring return for -25°C

Table 5 [V5] Pneumatically operated 4/2-way and 5/2-way valves

Name	Description
P 411 SR	Pneumatically actuated 4/2-way spool valves, with adjustable
	pneumatic pressure switch
P 411 SR VIT	Pneumatically actuated 4/2-way spool valves, with adjustable
1 411 51\ \text{VII}	pneumatic pressure switch, with FPM/FKM sealings
P 411 SR NT	Pneumatically actuated 4/2-way spool valves, with adjustable
1 411 51(11)	pneumatic pressure switch, for -20°C
PN 411 SR	Pneumatically actuated 4/2-way spool valves, with Namur
111 411 511	interface, with adjustable pneumatic pressure switch
	Pneumatically actuated 4/2-way spool valves, with Namur
PN 411 SR VIT	interface, with adjustable pneumatic pressure switch, with
	FPM/FKM sealings
PN 411 SR NT	Pneumatically actuated 4/2-way spool valves, with Namur
	interface, with adjustable pneumatic pressure switch, for -20°C
P 510	Pneumatically actuated 5/2-way spool valves
P 511	Pneumatically actuated 5/2-way spool valves with mechanical
1 511	spring return
P 510 VES	Pneumatically actuated 5/2-way spool valves, stainless steel
P 511 VES	Pneumatically actuated 5/2-way spool valves with mechanical
F 511 VL5	spring return, stainless steel
P 510 TT	Pneumatically actuated 5/2-way spool valves for low
F 310 11	temperature (with unidirectional sealing)
P 511 TT	Pneumatically actuated 5/2-way spool valves with mechanical
F 311 11	spring return for low temperature (with unidirectional sealing)



Name	Description
P 510 TT AIR	Pneumatically actuated 5/2-way spool valves for low
1 510 11 AIX	temperature (with bidirectional sealing)
P 511 TT AIR	Pneumatically actuated 5/2-way spool valves with mechanical
1 311 11 AllX	spring return, for low temperature (with bidirectional sealing)
P 510 VIT	Pneumatically actuated 5/2-way spool valves, with FPM/FKM
F 510 VII	sealings
P 511 VIT	Pneumatically actuated 5/2-way spool valves with mechanical
F 511 VII	spring return, with FPM/FKM sealings
P 510 NT	Pneumatically actuated 5/2-way spool valves for -20°C
P 511 NT	Pneumatically actuated 5/2-way spool valves with mechanical
F 311 IN1	spring return for -20°C
P 511 NTB	Pneumatically actuated 5/2-way spool valves with mechanical
F 311 INID	spring return for -25°C

Table 6 [V6] Pneumatically operated 5/3-way valves

Name	Description
P 53	Pneumatically actuated 5/3-way spool valves
P 53 VES	Pneumatically actuated 5/3-way spool valves, stainless steel
P 53 TT	Pneumatically actuated 5/3-way spool valves for low temperature (with unidirectional sealing)
P 53 TT AIR	Pneumatically actuated 5/3-way spool valves for low temperature (with bidirectional sealing)
P 53 VIT	Pneumatically actuated 5/3-way spool valves, with FPM/FKM sealings
P 53 NT	Pneumatically actuated 5/3-way spool valves for -25°C

Table 7 [V7] Pneumatically operated 6/2-way valves

Name	Description
P 611 SR	Pneumatically actuated 6/2-way spool valves, with adjustable pneumatic pressure switch
PN 611 SR	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch
PN 611 SR VIT	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch, with FPM/FKM sealings
PN 611 SR NT	Pneumatically actuated 6/2-way spool valves, with Namur interface, with adjustable pneumatic pressure switch for -20°C

Table 8 [V8] Pneumatically operated 6/2-way valves type PN 611 121 SR and its versions

Name	Description
PN 611 121 SR	Pneumatically actuated 6/2-way spool valves, G1/2", with
FN 011 121 3K	Namur interface, with adjustable pneumatic pressure switch
	Pneumatically actuated 6/2-way spool valves, G1/2", with
PN 611 121 SR VIT	Namur interface, with adjustable pneumatic pressure switch, with FPM/FKM sealings
	Pneumatically actuated 6/2-way spool valves, G1/2", with
PN 611 121 SR NT	Namur interface, with adjustable pneumatic pressure switch for - 20°C



Table 9 [V9] Pilot operated 2/2-way solenoid valves

Placeholder "__" for 24VDC, 110 VAC, 230 VAC.

Name	Description
M 210	Pilot operated 2/2-way solenoid valves
M 210 VES	Pilot operated 2/2-way solenoid valves, stainless steel
	Pilot operated 2/2-way solenoid valves for low temperature
M 210 TT	(with unidirectional sealing)
M 210 HT	Pilot operated 2/2-way solenoid valves for high temperature
M 210 NT	Pilot operated 2/2-way solenoid valves for -20°C
MC 210	Pilot operated 2/2-way solenoid valves with CNOMO interface
	Pilot operated 2/2-way solenoid valves with CNOMO interface,
MC 210 VES	stainless steel
M C 240 TT	Pilot operated 2/2-way solenoid valves with CNOMO interface,
MC 210 TT	for low temperature (with unidirectional sealing)
M O O4O NT	Pilot operated 2/2-way solenoid valves with CNOMO interface,
MC 210 NT	for -20°C
M 240 Fix d	Pilot operated 2/2-way solenoid valves with Ex d magnet
M 210 Ex d	system
M 240 VEC 57.4	Pilot operated 2/2-way solenoid valves, stainless steel, with Ex
M 210 VES Ex d	d magnet system
	Pilot operated 2/2-way solenoid valves with CNOMO interface,
MC 210 TT Ex d	for low temperature (with unidirectional sealing), with Ex d
	magnet system
M C 210 NT Evid	Pilot operated 2/2-way solenoid valves with CNOMO interface,
MC 210 NT Ex d	for -20°C, with Ex d magnet system
M 211	Pilot operated 2/2-way solenoid valves, with combined spring
IVI 211	return
M 211 V/ES	Pilot operated 2/2-way solenoid valves, with combined spring
M 211 VES	return, stainless steel
M 211 TT	Pilot operated 2/2-way solenoid valves, with combined spring
M 211 TT	return, for low temperature (with unidirectional sealing)
M 211 HT	Pilot operated 2/2-way solenoid valves, with combined spring
211	return, for high temperature
M 211 NT	Pilot operated 2/2-way solenoid valves, with combined spring
211 111	return, for -20°C
M C 211	Pilot operated 2/2-way solenoid valves with CNOMO interface,
MC 211	with combined spring return
MC 211 VES	Pilot operated 2/2-way solenoid valves with CNOMO interface,
	with combined spring return, stainless steel
N 0 044	Pilot operated 2/2-way solenoid valves with CNOMO interface,
MC 211 TT	with combined spring return, for low temperature (with
	unidirectional sealing)
MC 211 NT	Pilot operated 2/2-way solenoid valves with CNOMO interface,
	with combined spring return, for -20°C
M 211 Ex d	Pilot operated 2/2-way solenoid valves, with combined spring
	return, with Ex d magnet system
M 211 VES Ex d	Pilot operated 2/2-way solenoid valves, with combined spring
	return, stainless steel, with Ex d magnet system
M C 211 TT Fyd	Pilot operated 2/2-way solenoid valves, with combined spring
MC 211 TT Ex d	return, with CNOMO interface, for low temperature (with
MC 211 NT Ex d	unidirectional sealing), with Ex d magnet system Pilot operated 2/2-way solenoid valves, with combined spring
IVIO Z I I IN I EX U	Pilot operated 2/2-way solenoid valves, with combined spring



Name	Description
	return, with CNOMO interface, for -20°C, with Ex d magnet
	system

Table 10 [V10] Pilot operated 3/2-way solenoid valves

Placeholder "__" for 24VDC, 110 VAC, 230 VAC.

Name	Description		
M 310	Pilot operated 3/2-way solenoid valves		
M 310 VES	Pilot operated 3/2-way solenoid valves, stainless steel		
M 310 TT	Pilot operated 3/2-way solenoid valves for low temperature (with unidirectional sealing)		
M 310 TT AIR	Pilot operated 3/2-way solenoid valves for low temperature (with bidirectional sealing)		
M 310 HT	Pilot operated 3/2-way solenoid valves for high temperature		
M 310 NT	Pilot operated 3/2-way solenoid valves for -20°C		
MC 310	Pilot operated 3/2-way solenoid valves with CNOMO interface		
MC 310 VES	Pilot operated 3/2-way solenoid valves with CNOMO interface, stainless steel		
MC 310 TT	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)		
MC 310 TT AIR	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)		
MC 310 NT	Pilot operated 3/2-way solenoid valves with CNOMO interface, for -20°C		
M 310 Ex d	Pilot operated 3/2-way solenoid valves with Ex d magnet system		
M 310 VES Ex d	Pilot operated 3/2-way solenoid valves, stainless steel, with Ex d magnet system		
MC 310 TT Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system		
MC 310 TT AIR Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system		
MC 310 NT Ex d	Pilot operated 3/2-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system		
M 311	Pilot operated 3/2-way solenoid valves, with combined spring return		
M 311 VES	Pilot operated 3/2-way solenoid valves, with combined spring return, stainless steel		
M 311 TT	Pilot operated 3/2-way solenoid valves, with combined spring return, for low temperature (with unidirectional sealing)		
M 311 TT AIR	Pilot operated 3/2-way solenoid valves, with combined spring return, for low temperature (with bidirectional sealing)		
M 311 HT	Pilot operated 3/2-way solenoid valves, with combined spring return, for high temperature		
M 311 NT	Pilot operated 3/2-way solenoid valves, with combined spring return, for -20°C		
M 311 NTB	Pilot operated 3/2-way solenoid valves, with combined spring return, for -25°C		
MC 311	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return		



Name	Description		
MC 311 VES	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, stainless steel		
MC 311 TT	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with unidirectional sealing)		
MC 311 TT AIR	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with bidirectional sealing)		
MC 311 NT	Pilot operated 3/2-way solenoid valves with CNOMO interface, with combined spring return, for -20°C		
M 311 Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with Ex d magnet system		
M 311 VES Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, stainless steel, with Ex d magnet system		
MC 311 TT Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system		
MC 311 TT AIR Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system		
MC 311 NT Ex d	Pilot operated 3/2-way solenoid valves, with combined spring return, with CNOMO interface, for -20°C, with Ex d magnet system		

Table 11 [V11] Pilot operated 5/2-way solenoid valves

Placeholder "__" for 24VDC, 110 VAC, 230 VAC.

Name	Description		
M 510	Pilot operated 5/2-way solenoid valves		
M 510 VES	Pilot operated 5/2-way solenoid valves, stainless steel		
M 510 TT	Pilot operated 5/2-way solenoid valves for low temperature (with unidirectional sealing)		
M 510 TT AIR	Pilot operated 5/2-way solenoid valves for low temperature (with bidirectional sealing)		
M 510 HT	Pilot operated 5/2-way solenoid valves for high temperature		
M 510 NT	Pilot operated 5/2-way solenoid valves for -20°C		
MC 510	Pilot operated 5/2-way solenoid valves with CNOMO interface		
MC 510 VES	Pilot operated 5/2-way solenoid valves with CNOMO interface, stainless steel		
MC 510 TT	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)		
MC 510 TT AIR	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)		
MC 510 NT	Pilot operated 5/2-way solenoid valves with CNOMO interface, for -20°C		
M 510 Ex d	Pilot operated 5/2-way solenoid valves with Ex d magnet system		
M 510 VES Ex d	Pilot operated 5/2-way solenoid valves, stainless steel, with Ex d magnet system		



Name	Description		
MC 510 TT Ex d	Pilot operated 5/2-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system		
MC 510 TT AIR Ex d	Ex d magnet system		
MC 510 NT Ex d	Pilot operated 5/2-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system		
M 511	Pilot operated 5/2-way solenoid valves, with combined spring return		
M 511 VES	Pilot operated 5/2-way solenoid valves, with combined spring return, stainless steel		
M 511 TT	Pilot operated 5/2-way solenoid valves, with combined spring return, for low temperature (with unidirectional sealing)		
M 511 TT AIR	Pilot operated 5/2-way solenoid valves, with combined spring return, for low temperature (with bidirectional sealing)		
M 511 HT	Pilot operated 5/2-way solenoid valves, with combined spring return, for high temperature		
M 511 NT	Pilot operated 5/2-way solenoid valves, with combined spring return, for -20°C		
M 511 NTB	Pilot operated 5/2-way solenoid valves, with combined spring return, for -25°C		
MC 511	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return		
MC 511 VES	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, stainless steel		
MC 511 TT	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with unidirectional sealing)		
MC 511 TT AIR	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for low temperature (with bidirectional sealing)		
MC 511 NT	Pilot operated 5/2-way solenoid valves with CNOMO interface, with combined spring return, for -20°C		
M 511 Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with Ex d magnet system		
M 511 VES Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, stainless steel, with Ex d magnet system		
MC 511 TT Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system		
MC 511 TT AIR Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system		
MC 511 NT Ex d	Pilot operated 5/2-way solenoid valves, with combined spring return, with CNOMO interface, for -20°C, with Ex d magnet system		



Table 12 [V12] Pilot operated 5/3-way solenoid valves

Placeholder "__" for 24VDC, 110 VAC, 230 VAC.

Name	Description		
M 53	Pilot operated 5/3-way solenoid valves		
M 53 VES	Pilot operated 5/3-way solenoid valves, stainless steel		
M 53 TT	Pilot operated 5/3-way solenoid valves for low temperature (with unidirectional sealing)		
M 53 TT AIR	Pilot operated 5/3-way solenoid valves for low temperature (with bidirectional sealing)		
M 53 HT	Pilot operated 5/3-way solenoid valves for high temperature		
M 53 NT	Pilot operated 5/3-way solenoid valves for -20°C		
MC 53	Pilot operated 5/3-way solenoid valves with CNOMO interface		
MC 53 VES	Pilot operated 5/3-way solenoid valves with CNOMO interface, stainless steel		
MC 53 TT	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing)		
MC 53 TT AIR	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing)		
MC 53 NT	Pilot operated 5/3-way solenoid valves with CNOMO interface, for -20°C		
M 53 Ex d	Pilot operated 5/3-way solenoid valves with Ex d magnet system		
M 53 VES Ex d	Pilot operated 5/3-way solenoid valves, stainless steel, with Ex d magnet system		
MC 53 TT Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with unidirectional sealing), with Ex d magnet system		
MC 53 TT AIR Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for low temperature (with bidirectional sealing), with Ex d magnet system		
MC 53 NT Ex d	Pilot operated 5/3-way solenoid valves with CNOMO interface, for -20°C, with Ex d magnet system		

Table 13 [V13] Pilot operated 2/2-way solenoid valves with auxiliary control air

Name	Description
MEH 211	Pilot operated 2/2-way solenoid valves with auxiliary control
IVILITZTT	air
MEH 211 VES	Pilot operated 2/2-way solenoid valves with auxiliary control
WE11211 VE3	air, stainless steel
MEH 211 TT	Pilot operated 2/2-way solenoid valves with auxiliary control
MEH 211 11	air, for low temperature (with unidirectional sealing)
MEH 211 HT	Pilot operated 2/2-way solenoid valves with auxiliary control
MEHZH III	air, for high temperature
MEH 211 NT	Pilot operated 2/2-way solenoid valves, with auxiliary control
WEITZII NI	air for -20°C



Table 14 [V14] Pilot operated 3/2-way solenoid valves with auxiliary control air

Name	Description
MEH 311	Pilot operated 3/2-way solenoid valves with auxiliary control
WIEH 311	air
MEH 311 VES	Pilot operated 3/2-way solenoid valves with auxiliary control
WE11311 VE3	air, stainless steel
MEH 311 TT	Pilot operated 3/2-way solenoid valves with auxiliary control
WE11311 11	air, for low temperature (with unidirectional sealing)
MEH 311TT AIR	Pilot operated 3/2-way solenoid valves with auxiliary control
WEITSTTTT AIR	air, for low temperature (with bidirectional sealing)
MEH 311 HT	Pilot operated 3/2-way solenoid valves with auxiliary control
WE11311 111	air, for high temperature
MEH 311 NT	Pilot operated 3/2-way solenoid valves, with auxiliary control
WIEIT 311 INT	air for -20°C

Table 15 [V15] Pilot operated 5/2-way solenoid valves with auxiliary control air

Name	Description
MEH 511	Pilot operated 5/2-way solenoid valves with auxiliary control air
MEH 511 VES	Pilot operated 5/2-way solenoid valves with auxiliary control air, stainless steel
MEH 511 TT	Pilot operated 5/2-way solenoid valves with auxiliary control air, for low temperature (with unidirectional sealing)
MEH 511 TT AIR	Pilot operated 5/2-way solenoid valves with auxiliary control air, for low temperature (with bidirectional sealing)
MEH 511 HT	Pilot operated 5/2-way solenoid valves with auxiliary control air, for high temperature
MEH 511 NT	Pilot operated 5/2-way solenoid valves, with auxiliary control air for -20°C

Table 16 [V16] Pilot operated 5/3-way solenoid valves with auxiliary control air

Name	Description
MEH 53	Pilot operated 5/3-way solenoid valves with auxiliary control
WE1133	air
MEH 53 VES	Pilot operated 5/3-way solenoid valves with auxiliary control
WE1133 VE3	air, stainless steel
MEH 53 TT	Pilot operated 5/3-way solenoid valves with auxiliary control
WE1133 11	air, for low temperature (with unidirectional sealing)
MEH 53 TT AIR	Pilot operated 5/3-way solenoid valves with auxiliary control
WEIT 55 IT AIR	air, for low temperature (with bidirectional sealing)
MEH 53 HT	Pilot operated 5/3-way solenoid valves with auxiliary control
WEH 55 H1	air, for high temperature
MEH 53 NT	Pilot operated 5/3-way solenoid valves, with auxiliary control
WIEI I 33 IN I	air for -20°C

A number of logic-elements, bi-stable and quick-exhaust variants were also subject of the assessment for Systematic Capability. As they share the same development process, verification and testing as the Variants listed above in Tables 1 - 16, the Logic-elements, bi-stable and quick-exhaust variants meet the same requirements for Systematic Capability as the variants. However, these Logic-elements, bi-stable and quick-exhaust variants are not generally suitable for safety applications, so no FMEDA analysis was done for these variants.



2.1 Failure rates

The table below lists the failure rates in FIT (failures / 109 hours) for the variants listed above.

Table 17: Failure rates per IEC 61508:2010

			exida Profile	
Variant	Profile	Failure rates (in FIT)		
		λ _{SD}	λ_{DD}	λου
[V1]	5	3	0	377
[V2]	5	3	0	545
[V3]	5	75	0	7
[V4]	5	55	0	330
[V5]	5	55	0	470
[V6]	5	96	0	502
[V7]	5	55	0	540
[V8]	5	111	0	870
[V9]	5	159	0	206
[V10]	5	150	0	230
[V11]	5	150	0	470
[V12]	5	280	0	504
[V13]	5	159	0	280
[V14]	5	145	0	331
[V15]	5	145	0	471
[V16]	5	269	0	504



3 Status of the Document

3.1 Liability

exida prepares reports based on methods advocated in International standards. *exida* accepts no liability whatsoever for the use of this annex or for the correctness of the standards on which the general calculation methods are based.

3.2 Releases

Contract Number	Report Number	Revision Notes
Q23/04-151-C	1511-126-C R003 V3, R1	Naming corrected for M and P
Q23/04-151-C	1511-126-C R004 V3, R0	Surveillance audit 2023 New grouping structure implemented.
Q19/02-018-C	1511-126-C R004 V2, R0	Surveillance audit and new versions added: MEH, TT AIR and MH 311
Q15/11-126-C	1511-126-C R004 V1, R0	Review comments implemented
Q15/11-126-C	1511-126-C R004 V0, R1	Draft; Waiting for review

Author: Peter Söderblom

Review: Steven Close V2 R0

Jürgen Hochhaus V3 R0

Release status: Released 09-Jan-2020, V2 R0

24-Jan-2024, V3 R0 30-Jan-2024, V3 R1

3.3 Future Enhancements

At request of client.

3.4 Release Signatures

let I

Peter Söderblom, Senior Safety Engineer

Jürgen Hochhaus, Senior Safety Engineer